

sewoo

Mobile Premium Series

# SLK-TE25



- Printing speed and Compatibility
- Front paper loading & exit design
- Superior spill-proof with a sealed top.
- High speed printing at Max.7.9ips (200mm/sec.)
- Maximize productivity with Compact and Sleek design
- Reduce power consumption and cost through energy star certification.
- High reliability mechanism: 1.5 Million of Cutter life and 160km of TPH Life.



Barcode



Durable

80mm

Paper  
Width



Easy  
Loading



High  
Speed



Compact  
Design



Easy  
Maintenance



Energy  
Star

## APPLICATION



## SPECIFICATIONS



### PRINTER CHARACTERISTICS

#### Print Method

Direct thermal

#### Print Speed

Up to 7.9ips(200mm/sec)

#### Print Width

Up to 2.8" (72mm)

#### Resolution

180 dpi

#### Power

Power type : External SMPS

AC : 100~240Vac 50/60Hz

DC : 24Vdc / 1.75A

#### Sensor

Standard: Paper end, Paper low,  
Cover open

Optional: Black mark

#### Reliability

TPH life : 160km

MCBF : 60 Million lines

Cutter life : 2.0 Million cuts

#### Drawer port

2 Circuit(24V, 1A Max.)



### PHYSICAL CHARACTERISTICS

#### Dimension (W x D x H)

4.42" x 7.87" x 4.92"  
(112.5 x 200 x 125mm)

#### Weight

3.0lb(1.4Kg)



### INTERFACES

#### Standard

USB(B type)

#### Option

Serial(RS-232C),

Parallel(IEEE1284),

Ethernet, Wi-Fi(802.11b),

Bluetooth Ver 2.1(Movon,iOS)

Bluetooth Ver 4.2(Movon,iOS)



### CERTIFICATIONS

CE, FCC, KC, UL/cUL,

ENERGY STAR, Mfi



### OPERATING CHARACTERISTICS

#### Operating Temperature

41 ~ 104°F( 5 ~ 40°C)

#### Operating Humidity

35 ~ 80%

#### Storage Temperature

-4 ~ 140°F(-20 ~ 60°C)

#### Storage Humidity

10 ~ 90%



### MEDIA CHARACTERISTICS

#### Media Type

Thermal receipt paper

#### Media Width

2.32", 3.14"(59, 80mm)

#### Media Core Diameter

0.4"(12.5mm)

#### Media Roll Diameter

3.2"(ø 83mm)

#### Thickness

0.06~0.09mm



### SOFTWARE

#### Emulations

ESC/POS Command compatible

#### Drivers

Windows Driver(XP ~, Server2003 ~),  
Windows CE & Mobile Driver (CE 4.2 ~,  
Mobile 5.0 ~), Linux Driver, Mac Driver,  
OPOS Driver, JavaPOS Driver, iOS SDK,  
Android(6.0 ~) SDK, Windows SDK,  
Windows CE SDK, Linux SDK



### BARCODES

#### 1D

EAN-8, EAN-13, Code 39, Code 93,  
Code 128, ITF, UPC-A, UPC-E, Codabar  
2D

QR, PDF417, Datamatrix



### FONTS / GRAPHICS

#### Character Type

Font A(12x24), Font B(9x17),  
Chinese(Traditional/Simplified, 24x24),  
Korean(24x24), Japanese(24x24)

#### Characters per line (CPL)

Font A(12x24) : 42cpl,  
Font B(9x17) : 56cpl,  
Chinese/Korean/Japanese: 21cpl

#### Character set

95 Alphanumeric,  
14 International,  
128 x 18 Graphic



### ACCESSORIES

#### Standard

Power Adaptor 24Vdc / 1.75A

#### Option

Melody Box



### COLOR

Black, Ivory

# sewoo

Republic of Korea [Head Office / R&D Center]

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 18103, Republic of Korea

T. +82-31-8077-5000 F. +82-31-624-5310 E. sales@miniprinter.com

www.miniprinter.com

#### USA, Inc.

Torrance, CA 90502, USA

T. +1-310-617-7401

E. NA\_sales@miniprinter.com

#### México Office

Cuahtémoc, D.F. Mexico. CP 06500

T. +52-1-55-3232-9543 M. +52-1-55-143893

E. LA\_sales@miniprinter.com

#### China Office

Shang hai shi, Song jiang qu

T. +86-177-1729-9100

E. sales@miniprinter.com

