sewoo

Linerless Printer

SLK-SL103

- Supports Multiple Media Types
(CPCL/ESCPOS/ZPL Command compatible)
- Space-saving vertical design with dual paper exit (Front&Top)
Reduce waste improve efficiency with linerless printing.
- Order reminder alarm with volume control
- Specialized back-feed function
- Automatic media-specific print width adjustment
- Detects label removal to trigger next print

Built-in
Melody Box

Auto Width
Adjust

Paper
Saving (20%)

Takeoff
Sensor

APPLICATION

SPECIFICATIONS

PRINTER CHARACTERISTICS

Print Method
Direct thermal(Front & Top Exit)
Print Speed
Linerless : 180mm/s, Receipt :250mm/s
Print Width
32 / 48 / 60 / 72 / 80 mm
Resolution
203 DPI
Power
Power type : External SMPS
AC : 100~240Vac 50/60Hz
DC : 24Vdc / 1.75A
Sensor
Standard: Paper end, Cover open,
Paper width Detection, Gap, Take-off
Reliability
TPH life : 160km
MCBF : 60 Million lines
Cutter life : 1.0 Million cuts
Drawer port
2 Circuit(24V, 1A Max.)

PHYSICAL CHARACTERISTICS

Dimension (W x D x H)
57" x 57.5" x 83.8"
(145 x 146 x 213mm)
Weight
1.57kg

INTERFACES

Standard
USB(B type) + Ethernet
+ Serial(RS-232 9pin)
Option : U + S, U + E
Option
Bluetooth : Smart Ready
(Bluetooth5.2+BLE),
Wi-Fi : 802.11a/b/g/n

CERTIFICATIONS

CE, FCC, KC, UL/cUL,
ENERGY STAR, Mfi

OPERATING CHARACTERISTICS

Operating Temperature
0 ~ 45°C
Operating Humidity
35 ~ 80%
Storage Temperature
-20 ~ 60°C
Storage Humidity
10 ~ 90%

MEDIA CHARACTERISTICS

Media Type
Thermal receipt paper, Blackmark,
Linerless(Permanent), Gap Label,
BluePaper
Media Width
39± 0.5 / 57± 0.5 / 61± 0.5 /
79± 0.5 / 82± 0.5 mm
Media Core Diameter
Linerless : Min.1inch
Other : 12.5mm ± 0.5mm
Media Roll Diameter
Max. ø 105mm
Thickness
ESCPOS : 0.05 ~ 0.08 mm,
CPCL / ZPL : 0.06 ~ 0.15 mm

SOFTWARE

Emulations
CPCL/ESCPOS/ZPL
Command compatible
Drivers
Windows Driver(XP ~, Server2003 ~),
Linux Driver, Mac Driver, OPOS Driver,
JavaPOS Driver, iOS SDK, Android(6.0 ~)
SDK, Windows SDK, Linux SDK

BARCODES

1D
EAN-8, EAN-8(+2+5), EAN-13,
EAN-13(+2+5), Codabar, Code11,
Code39, Code93, Code128, ITF,
UPC-A(+2+5), UPC-E, UPC-E(+2+5),
Planet, etc
2D
QR, PDF417, MicroPDF417,
Maxicode, Datamatrix, Aztec,
RSS14, TLC39

COLOR

Black, Ivory

FONTS / GRAPHICS

Character Type
FontA(12x24), FontB(9x17),
Font0/1/2/4/5/6/7,
TTF Font0, FontA~H, FontGS
Font1~8, Asian Font(KOR, JPN,
CHN_GB2312, CHN_BIG5),
Resident TTF, Downloadable TTF,
Downloadable Bitmap
Characters per line (CPL)
Font A(12x24) :
21/32/40/48/ 53 columns
Font B(9x17) :
28/42/53/64/71 columns
Character set
Alpha Numeric Character : 95
Expended Graphic :
128x18 Page (1 space page)
nternational Character : 14

ACCESSORIES

Melody box, 24V Internal/External Buzzer
Types Paper Guide :
Standard
83mm, 80mm, 62mm, 58mm, 40mm
Option
38mm

sewoo

Republic of Korea [Head Office / R&D Center]
28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi- do, 18103, Republic of Korea
T. +82-31-8077-5000 **F.** +82-31-624-5310 **E.** sales@miniprinter.com

www.miniprinter.com

USA, Inc.
Torrance, CA 90502, USA
T. +1-310-617-7401
E. NA_Sales@miniprinter.com

México
Cuauhtémoc, Mexico D.F.
T. +52-1-55-143893 **M.** +52-1-55-3232-9543
E. LA_Sales@miniprinter.com